





RR 100 Profi I

Crawler

Exploitation:
pushing:  100 - 300 mm  $\geq \varnothing 100 \text{ mm}$, 87°

RR 100 Profi II

Exploitation:
driving:  100 - 600 mm  $\geq \varnothing 150 \text{ mm}$, 45°

A very robust and traction forced crawler.
About the system of wheels and chains is this
crawler best adapted for problematic pipes.
Digital camera system.

ART. NO.: see page 24

COMPATIBILITY:

– Extensible with the axial camera head RIK 55/70

CAMERA HEAD, Model: RSK 78/110

Detailed description, see page 2

CRAWLER

CABLE DRUM

- Stable cable drum in steel plate
- 70 - 120 metre extrem stable
Camera cable
- Cable lenght handing standard:
70 metre (other lenghts: extra charge)
- Adjustable brake
- Trouble-free slip-ring

CONTROL CASE

Images are showing the systems with possible features.

- Version Profi I : Control case **Standard**
- Version Profi II : Control case **Komfort**

Power supply: 230 / 115 V AC

Ready to take on difficult working conditions.

By adapted and modular accessories
(see page 32, not in scope of delivery) such as:

- Wheels of different sizes from different materials and
with different profiles,
- Different types of extra searchlight,
- With camera elevator,
the crawler can be individually adapted to many
different working conditions.

Photo, as of As of $\varnothing 150 \text{ mm}$:



**INFO RESUMEN
del ORIGINAL**
Para envío por email

GIMATEG
INSTRUMENTOS y EQUIPOS TECNICOS
info@gimateg.com 937071855



Set-example: Profi II with
options and accessories

	RR 100 Profi I	RR 100 Profi II
Art. no.	78110.050	78110.051

CONTROL CASE inclusive:
and:



Standard	Komfort
	

Choose the further
components individually, see points:

① - ③

① OPTIONS of the cable drum

Longer camera cable (price per metre, up to max. 120 metre)	5560.029
----------------------------------------------------------------	----------

② OPTIONS of the control cases

Data-input to the metre fade-in in picture (requires *)	●	●	9090.003
Data-input to the metre fade-in in picture + PC interface (RS232) (requires *)	●	●	9090.004
Digital-Videorecorder (see page 33) documentation on SD-card Operation over remote control	●	—	9090.006
Documentation-PC with DVD writer (see page 28)	—	●	9090.020
easyCAM inspection software for the Documentation-PC (see page 29)	—	●	8080.200

③ ACCESSORIES

Pluggable Locating sender (33 kHz)	7070.050
Pluggable Locating sender (512 Hz)	7070.051
Axial camera head RIK 55/70	5570.001
see page 32	→



pluggable Locat ng sender

SÓLO INFORMATIVO